



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont
Material Safety Data Sheet

Page 1

DuPont(TM) StoneTech(R) Professional Revitalizer(R) Cleaner &
Protector Conc.
6451CR Revised 11-OCT-2008

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont StoneTech(R) Professional
370 North Wiget Lane, Suite 200
Walnut Creek, CA 94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000
Transport Emergency : CHEMTREC: 800-424-9300/Outside US:
703-527-3887
Medical Emergency : 800-441-3637/Outside US: 302-774-1000

COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
N-Alkyl (C12-16) Dimethylamine Oxides		
Propylene Glycol n-Butyl Ether	5131-66-8	
Isopropanol	67-63-0	
Fluorinated Acrylic Copolymer		

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation: May cause respiratory irritation.

Skin Contact: May cause skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: Harmful if swallowed.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

FIRST AID MEASURES

First Aid

INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point : 125 F (52 C)
Method : Pensky-Martens Closed Cup - PMCC.

Non-flammable.

Extinguishing Media

Use media appropriate for surrounding material.

Fire Fighting Instructions

Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

(ACCIDENTAL RELEASE MEASURES - Continued)

Wear self-contained breathing apparatus (SCBA) and full protective gear.

Initial Containment

Dike spill.

Spill Clean Up

Soak up with sawdust, sand, oil dry or other absorbent material.

HANDLING AND STORAGE

Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling.

Handling (Physical Aspects)

Keep container tightly closed.

Storage

Store in a cool, dry place.

Avoid freezing or extended storage in high temperature.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use only with adequate ventilation.

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses. Where splash potential exists, wear chemical splash goggles.

RESPIRATORS

Wear NIOSH approved respiratory protection, as appropriate.

PROTECTIVE CLOTHING

Where there is potential for skin contact have available and wear as appropriate impervious gloves, apron, pants and jacket.

Exposure Guidelines

Applicable Exposure Limits

Propylene Glycol n-Butyl Ether

AEL * (DuPont) : 50 ppm, 8 & 12 Hr. TWA

Isopropanol

PEL (OSHA) : 400 ppm, 980 mg/m3, 8 Hr. TWA

TLV (ACGIH) : 200 ppm, 8 Hr. TWA, A4

STEL 400 ppm

AEL * (DuPont) : 200 ppm, 8 & 12 Hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

pH : 5.5-6.5
Odor : (mild), Sweet.
Form : Liquid.
Specific Gravity : 1.02

STABILITY AND REACTIVITY

Chemical Stability

Stable.

Incompatibility with Other Materials

Incompatible with strong alkaline compounds, acids and oxidizing agents.

Decomposition

Thermal decomposition may produce carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen fluoride and acrid smoke.

Polymerization

Polymerization will not occur.

DISPOSAL CONSIDERATIONS

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

TRANSPORTATION INFORMATION

Shipping Information

DOT - not regulated in packages with a capacity of less than 119 gallons.

IMDG/IATA

UN Number,,: 1993
Proper Shipping Name,: Flammable Liquid, N.O.S.
(Isopropanol, 1-Butoxy-2-Propanol)
Hazard Class,,: 3
Packing Group,,: III
Label,,,: Flammable Liquid

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS